

Dati tecnici

Velocità Fissa

VELOCITA' FISSA	Bar	HP	kW	l/min	m3/h	dB(A)	Diam. uscita aria	kg base
CPE 150								
CPE 150/7,5	7,5	180	132	19560	1173,6	75	2"	1810
CPE 150/8,5	8,5	180	132	18960	1137,6	75	2"	1810
CPE 150/10	10	180	132	17100	1026,0	75	2"	1810
CPE 150/13	13	180	132	14640	878,9	75	2"	1810
CPF 175 - 340								
CPF 175/7,5	7,5	180	132	23588	1415,2	75	3"	2600
CPF 175/8	8	180	132	22625	1357,5	75	3"	2600
CPF 175/10	10	180	132	20530	1231,8	75	3"	2600
CPF 175/13	13	180	132	16849	1010,9	75	3"	2600
CPF 200/7,5	7,5	220	160	28628	1717,6	73	3"	2830
CPF 200/8	8	220	160	27354	1641,2	73	3"	2830
CPF 200/10	10	220	160	24833	1489,9	73	3"	2830
CPF 200/13	13	220	160	20530	1231,8	73	3"	2830
CPF 270/7,5	7,5	270	200	35500	2130,0	77	4"	4710
CPF 270/8,5	8,5	270	200	32700	2130,0	77	4"	4710
CPF 270/10	10	270	200	30800	1962,0	77	4"	4710
CPF 270/13	13	270	200	26200	1572,0	77	4"	4710
CPF 340/7,5	7,5	340	250	40800	2448,0	78	4"	4780
CPF 340/8,5	8,5	340	250	40000	2400,0	78	4"	4780
CPF 340/10	10	340	250	37600	2256,0	78	4"	4780